



PLUGIN 726 :NEW TRASDATA

Microprocessor side



Microprocessor's opposite side





DIRECT CONNECTION

In order to connect to the ECU use the CABLE F32GN037C.

Make sure that the POWER led (red) on NEW TRASDATA is ON. These connections are required for all the connection approaches: loose wires and metal positioning frame adapter.

COLORE FILO WIRE COLOUR	DESCRIZIONE DESCRIPTION
ROSSO RED	POSITIVO DIRETTO POWER BATTERY
ARANCIO ORANGE	POSITIVO SOTTO QUADRO POWER SWITCH ON
NERO BLACK	MASSA GND
GIALLO YELLOW	KLINE
VERDE GREEN	CAN LOW
BIANCO WHITE	CAN HIGH
GRIGIO GREY	POL4 BOOT
BLU BLUE	POL5 CNF1
VIOLA/GRIGIO PURPLE/GREY	TENSIONE PROG. PROG. VOLTAGE
MARRONE BROWN	RESET

**ECU CONNECTOR**

J-TAG LOOSE WIRES CONNECTION


Connect the cable F34NTF53 as shown here

			
Pin	Colore Coulor		
11	Non usato Not used		
12	Non usato Not used		
13	Non usato Not used		
14	Non usato Not used		
15	Verde / Green		
16	Blu Blue		
17	Non usato Not used		
18	Grigio Grey		
19	Bianco White		
20	Nero Black		
21	Non usato Not used		
22	Rosso Red		
23	Non usato Not used		
24	Giallo Yellow		
25	Non usato Not used		
26	Non usato Not used		


Warning : to enable the J-TAG communication it is necessary to perform the 5 short-circuits LINKS as displayed in the following pictures.


The ECU can be placed back in the vehicle without removing the short-circuits LINK

Microprocessor side





Microprocessor's opposite side





METAL POSITIONING FRAME CONNECTION

For the metal positioning frame connection is required the F34DM025 adapter.



JTAG pads for the communication are placed below the microprocessor, for this connection the bridges (LINK) shown at pg. 6 are required. Check the PIN 1 position for a correct orientation of the adapter F34DM025.

